

Heavy Duty Automatic Tripod Turnstile

ETA-2000A



Specification

Passage Width : =550mm
Throughput rate : 35p/m
Power Supply : 100 ~240V
Operational Voltage : 24V
Max tolerance of Arms : 80 Kg
Angle per rotation : 120 °
Operation Type : Oneway - Bidirectional
Flow Rate : 25-48 passages/minute
Input control signal : Dry contact
Max Power Consumption : 30 W
Frequency : 50~60hz
Protection Level : IP 54
Working Temperature : -25 ~ +70°C
Electro - magnetic Drive : DC
Dimension Excluding Bar : 1200x280x980 mm
Net Weight Including Bar : 52kg
Opening Duration : 5s - 60s

Features:

Controller

- ▶ Full-Auto mode
- ▶ Single or Bi-directional function in mechanical and electrical versions

- ▶ Automatic reset of barrier arms after each passage
- ▶ Adjustable time out delay
- ▶ Operating Mode
- ▶ Single passage in the set direction
- ▶ Bi-directional passage
- ▶ Free passage in the set direction
- ▶ Always free or locked

Materials

- ▶ Housing : Made in metal sheet and painted, in or stainless steel AISI 304 or AISI 316
- ▶ Barrier Arms : Stainless steel
- ▶ Lid (Optional) : Stainless steel or artificial stone (black / brown)

Colours & Finishes

- ▶ High quality powder coating plus lacquered finish
- ▶ Dark grey color high quality powder coating plus lacquered finish
- ▶ Sandpaper powder coating with pearl mica effect

Disclaimer: Brief specifications are mentioned here. Specifications may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development

www.esslsecurity.com