

Multi-Biometric Time Attendance & Access Control System

SilkBio-101TC



Specification

Storage Capacity

Face Capacity : 2,000
Fingerprint Capacity : 3,000
ID Card Capacity : 3,000
Transaction Capacity : 1,00,000

Communication

TCP/IP, USB-Host, Wi-Fi(Optional)
Push Data : Yes

Standard Functions

Work Code, SMS, DST, Scheduled-bell, Self-Service Query,
Automatic Status Switch Photo ID, T9 Input, Camera, 9 digit user ID,
Built-in Battery, Multiple Verify Mode, External Bell
Access Control Interface : Lock, Door Sensor, Exit Button, Alarm

Optional

Optional Functions : Mifare

Visual

Display : 2.8-inch TFT Screen

Power & Environment

Operating Temperature : 0°C ~ 45°C
Power Supply : DC 12V --- 1.5A
Operating Humidity : 20% - 80%
Dimensions (in mm) : (L)180 x (W)154 x (H)34.2

Features

- Multi-biometric fast verification
- Touch Keypad
- Infrared auto-turning on function to save power
- Quick recognition of dry, wet and rough fingers
- Multi-language supported
- Built-in 2000mAh backup battery to extend operation time
- Prevents duplicated face registration and supports fake face detection function